

PREMIUM MOTOR OIL

TRUCKS & COMMERCIAL VEHICLES



**QUALITY
PERFORMANCE**

MANUFACTURED IN BELGIUM



5W40 PRO-TEC ULTRA
FULLY SYNTHETIC

PERFORMANCE LEVEL

ACEA: E7-12, E9-12
API: CJ-4/SM
MB-Approval 228.31
MAN: M 3575
Volvo: VDS-4
Mack EO-O Premium Plus, Renault VI RLD-3
Meets the requirements of Cummins CES 20081
Detroit Diesel 93K218/93K215/93K214
Cat: ECF-2/ECF-3

APPLICATIONS

This heavy duty engine oil is suitable for use in both on-road and off-highway applications. This engine oil contributes to low exhaust emission and particle levels benefits highly to the lifetime of emission control systems. This product complies with and exceeds the requirements of API CJ-4. By meeting the requirements of OEM's in Europe and North America this product has a wide choice of application possibilities. This product can be applied in Euro 5 engines with SCR exhaust gas system and in Euro 3 and Euro 4 engines when indicated by the manufacturer.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.856
Viscosity -30 °C	mPas	5740.00
Viscosity 40 °C	mm ² /s	88.40
Viscosity 100 °C	mm ² /s	13.90
Viscosity Index		161.00
Flash Point COC	°C	220.00
Pour Point	°C	-36.00
Total Base Number	mgKOH/g	10.30
Sulphate Ash	%	0.95