

**PREMIUM**  
**TRANSMISSION OIL**  
**TRUCKS & COMMERCIAL VEHICLES**



**QUALITY PERFORMANCE**

**MANUFACTURED IN BELGIUM**



**75W80 POLY GEAR MTF**  
**FULLY SYNTHETIC**

**PERFORMANCE LEVEL**

MAN: 341 E-3  
MAN: 341 Z-4  
MB: 235.4  
VOLVO: 97305

ZF: TE-ML 01L  
ZF: TE-ML 02L  
ZF: TE-ML 08  
ZF: TE-ML 16K

**APPLICATIONS**

This product meets the requirements of many commercial vehicle builders and/or gearbox manufacturers, including DAF, IVECO, Eaton Europe (300.000 km or 3 years), Renault (in accordance with B0032/2 Annex 3) and Volvo.

**AVAILABLE SIZE**



**CHARACTERISTICS/SPECS**

**UNIT**

**AVERAGE VALUE**

Density at 15 °C	kg/l	0.858
Viscosity 40 °C	mm <sup>2</sup> /s	65.00
Viscosity 100 °C	mm <sup>2</sup> /s	10.00
Viscosity Index		156.00
Flash Point COC	°C	218.00
Pour Point	°C	-45.00