

**PREMIUM  
MOTOR OIL**  
**PASSENGER CARS & SUVs**



**QUALITY  
PERFORMANCE**

**MANUFACTURED IN BELGIUM**



**5W30 DX**  
**FULLY SYNTHETIC**

**PERFORMANCE LEVEL**

ACEA: C3-12  
API: SN/CF  
BMW: LONGLIFE-04  
VW: 502 00  
VW: 505 00  
VW: 505 01

**AVAILABLE SIZE**



**APPLICATIONS**

This dexos 2™ approved oil is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2™ specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2™ lubricants. C2\* meets all engine protection requirements of ACEA C2.

**CHARACTERISTICS/SPECS**

**UNIT**

**AVERAGE VALUE**

Density at 15 °C	kg/l	0.851
Viscosity -30 °C	mPas	6136.00
Viscosity 40 °C	mm <sup>2</sup> /s	72.60
Viscosity 100 °C	mm <sup>2</sup> /s	12.50
Viscosity Index		172.00
Flash Point COC	°C	230.00
Pour Point	°C	-36.00
Total Base Number	mgKOH/g	7.40
Sulphate Ash	%	0.78