

PREMIUM MOTOR OIL

PASSENGER CARS & SUVs



**QUALITY
PERFORMANCE**

MANUFACTURED IN BELGIUM



15W40 PRO-TEC MINERAL

PERFORMANCE LEVEL

API: SJ/CG-4, CF
MB: 228.1, 229.1
ACEA: A3-B3-10, B3 -B4-08, E2-level
MAN: M-3275-1
VOLVO: VDS level
CAT: TO-2
ALLISON: C4

APPLICATIONS

Universal engine oil for four stroke diesel engines operating at high speed, heavy-duty vehicles (less than 0.05 wt% sulfur), as well as construction equipment (less than 0.5 wt% sulfur). This oil is ideal for engines designed to meet emission standards of 1994. This oil can be used in all gasoline engines in order to comply with strict operating rules.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.883
Viscosity 40 °C	mm ² /s	110.60
Viscosity 100 °C	mm ² /s	14.70
Viscosity Index		137.00
Flash Point COC	°C	230.00
Pour Point	°C	-30.00
Total Base Number	mgKOH/g	10.20
Sulphate Ash	%	1.29
Viscosity -20 °C	mPas	6600.00