

PREMIUM MOTOR OIL

TRUCKS & COMMERCIAL VEHICLES



QUALITY
PERFORMANCE

MANUFACTURED IN BELGIUM



**15W40 PRO-TEC ULTRA
SEMI SYNTHETIC**

PERFORMANCE LEVEL

ACEA: E7-12	GLOBAL: DHD-1
ACEA: E9-12	JASO: DH-2
API: CJ-4/SM	MACK: EO-O Premium Plus
CATERPILLAR: ECF-2	MAN: M3575
CATERPILLAR: ECF-3	MB: 228.31
CUMMINS: CES 20081	MTU: Type 2.1
DETROIT DIESEL: 93K218	RENAULT: RLD-3
DEUTZ: DQC-III-10 LA	VOLVO: VDS-4

APPLICATIONS

Suitable for all four-stroke diesel engines of trucks, with or without catalysts (e.g. SCR) or particulate filter. Meets most American and European manufacturers requirements and can also be used in older engines (Euro III and IV).

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.874
Viscosity 40 °C	mm ² /s	108.70
Viscosity 100 °C	mm ² /s	14.50
Viscosity Index		137.00
Flash Point COC	°C	232.00
Pour Point	°C	-36.00
Total Base Number	mgKOH/g	8.00
Sulphate Ash	%	0.92
Viscosity -25 °C	mPas	6880.00