

PREMIUM ATF AUTOMATIC TRANSMISSION FLUID



QUALITY
PERFORMANCE

MANUFACTURED IN BELGIUM



ATF PRO CVT FULLY SYNTHETIC

PERFORMANCE LEVEL

Meets the requirements of	3309/3324, Isuzu Besco ATF
Toyota ATF T-III/T-IV/D-II/WS	II/III
Nissan Matic Fluid C/D/J/K	Allison: C4/TES-228, JASO M
Honda ATF-Z1 (except in CVTs)	315-2013 Type 1A
Mazda ATF M-V	BMW: 7045E/8072B
Hyundai/Kia SP-II/SP-III	Chrysler: ATF +3/ATF +4
Suzuki ATF 3314	VAG: G-055-025
GM Dexron IID/IIIE/IIIG/IIIH, TASA	Volvo: 1161540
Ford Mercon/M2C	ZF: TE-ML 09/11A/11B
138CJ/166H/922A1/924A	Subaru: ATF/ATF 5AT/ATF
Aisin Warner: JWS	HP/Dexron II
	MB:
	236.1/236.6/236.7/236.8/23
	6.9/236.10

APPLICATIONS

This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.846
Viscosity 40 °C	mm ² /s	36.60
Viscosity 100 °C	mm ² /s	7.20
Viscosity Index		165.00
Flash Point COC	°C	212.00
Pour Point	°C	-48.00
Total Base Number	mgKOH/g	2.70