

PREMIUM MOTOR OIL

PASSENGER CARS & SUVs



**QUALITY
PERFORMANCE**

MANUFACTURED IN BELGIUM



5W40 SX

FULLY SYNTHETIC

PERFORMANCE LEVEL

ACEA: A3/B4-12	Fiat 9.55535-M2
API: SN/CF	PORSCHE: A40
BMW: LONGLIFE-01	PSA: B71 2296
MB: 226.5	RENAULT: RN 0700
MB: 229.3	RENAULT: RN 0710
OPEL: GM-LL-B-025	VW: 502 00
	VW: 505 00

APPLICATIONS

This oil is used in gasoline engines of cars, which demand the highest performance and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.856
Viscosity -30 °C	mPas	6100.00
Viscosity 40 °C	mm ² /s	86.00
Viscosity 100 °C	mm ² /s	14.40
Viscosity Index		175.00
Flash Point COC	°C	220.00
Pour Point	°C	-33.00
Total Base Number	mgKOH/g	9.60
Sulphate Ash	%	1.20