

**PREMIUM  
MOTOR OIL**  
**PASSENGER CARS & SUVs**



**QUALITY  
PERFORMANCE**

**MANUFACTURED IN BELGIUM**



**5W20 MF**  
**FULLY SYNTHETIC**

**PERFORMANCE LEVEL**

ACEA: A1/B1-12  
API: SN  
FORD: WSS-M2C948-B  
JAGUAR / LAND ROVER  
STJR.03.5004

**APPLICATIONS**

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or API SN.

**AVAILABLE SIZE**



**CHARACTERISTICS/SPECS**

**UNIT**

**AVERAGE VALUE**

Density at 15 °C	kg/l	0.851
Viscosity -30 °C	mm <sup>2</sup> /s	5500.00
Viscosity 40 °C	mm <sup>2</sup> /s	42.30
Viscosity 100 °C		7.90
Viscosity Index	°C	162.00
Flash Point COC	°C	220.00
Pour Point	mgKOH/g	-39.00
Total Base Number	%	7.60
Sulphate Ash	mPas	0.80