

PREMIUM ATF AUTOMATIC TRANSMISSION FLUID



QUALITY
PERFORMANCE

MANUFACTURED IN BELGIUM



ATF III MINERAL

PERFORMANCE LEVEL

ALLISON : C4	ZF: TE-ML 03D
FORD: MERCON	ZF: TE-ML 04D
GM: 6417-M DEXRON III-G	ZF: TE-ML 09
MAN: 339 V1/Z1	ZF: TE-ML 11B
MB: 236.5	ZF: TE-ML 14A
MB: 236.9	ZF: TE-ML 17C
VOITH: H55.6335xx	
VOLVO: STD 1273,40 (97340)	
VOLVO: STD 1273,41 (97341)	

APPLICATIONS

This oil is used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.855
Viscosity 40 °C	mm ² /s	33.90
Viscosity 100 °C	mm ² /s	7.10
Viscosity Index		179.00
Flash Point COC	°C	196.00
Pour Point	°C	-45.00
Brookfield Viscosity at -40 °C	mPas	17500.00
Color		Red