

PREMIUM MOTOR OIL

TRUCKS & COMMERCIAL VEHICLES



**QUALITY
PERFORMANCE**

MANUFACTURED IN BELGIUM



**10W30 PRO-TEC ULTRA
SEMI SYNTHETIC**

PERFORMANCE LEVEL

ACEA: E7-08 Issue 2
ACEA: E9-08 Issue 2
API: CJ-4/SM
CATERPILLAR: ECF-2
CATERPILLAR: ECF-3
CUMMINS: CES 20081

DEUTZ: DQC-III-10 LA
MACK: EO-O Premium Plus
MAN: M3575
MB: 228.31
RENAULT: RLD-3
VOLVO: VDS-4

APPLICATIONS

Suitable for all four-stroke diesel engines of trucks, with or without catalysts (e.g. SCR) or particulate filter. Meets most American and European manufacturers requirements and can also be used in older engines (Euro III and IV). This lower viscosity grade has been specifically developed to achieve better fuel economy.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.864
Viscosity 40 °C	mm ² /s	79.90
Viscosity 100 °C	mm ² /s	12.00
Viscosity Index		145.00
Flash Point COC	°C	226.00
Pour Point	°C	-36.00
Total Base Number	mgKOH/g	8.90
Sulphate Ash	%	1.00
Viscosity -25 °C	mPas	6120.00