

PREMIUM MOTOR OIL

TRUCKS & COMMERCIAL VEHICLES



QUALITY
PERFORMANCE

MANUFACTURED IN BELGIUM



5W30 PRO-TEC S

FULLY SYNTHETIC

PERFORMANCE LEVEL

ACEA: E4-12	MTU: Type 3
ACEA: E7-12	RENAULT: RD-2
API: CI-4	RENAULT: RLD
DAF: HP1/HP2	RENAULT: RLD-2
DEUTZ: DQC-IV-10	RENAULT: RXD
MACK: EO-N	SCANIA: LDF
MAN: M3277 / M3377	VOLVO: VDS-3
MB: 228.5	CAT: ECF-2
CUMMINS: 20076/20078	

APPLICATIONS

It is intended for truck fleet operators, seeking the best available lubricating oil technology, to meet the increasingly stringent exhaust limits imposed on diesel engines in Europe. Because of the very high detergency, this oil is not suitable for gasoline engines and vehicles equipped with particulate filters.

AVAILABLE SIZE



CHARACTERISTICS/SPECS

UNIT

AVERAGE VALUE

Density at 15 °C	kg/l	0.855
Viscosity -30 °C	mPas	6420.00
Viscosity 40 °C	mm ² /s	71.60
Viscosity 100 °C	mm ² /s	12.17
Viscosity Index		168.00
Flash Point COC	°C	224.00
Pour Point	°C	-39.00
Total Base Number	mgKOH/g	12.20
Sulphate Ash	%	1.35