

# PREMIUM ATF AUTOMATIC TRANSMISSION FLUID



QUALITY  
PERFORMANCE

MANUFACTURED IN BELGIUM



## ATF S 41 FULLY SYNTHETIC

### PERFORMANCE LEVEL

BENTLEY: PY112995PA	GM: DEXRON VI
BMW: 8322 2152426	JAGUAR: Fluid 8432
BMW: 8322 0144137	FORD: MERCON LV & SP
NISSAN: MATIC - S	LAND ROVER: TYK500050
SAAB: 93 165 147	MASERATI: 231603
TOYOTA: WS	VW: G 055 005 A1/A2/A6
BMW: M-1375.4 (8322	VW: G 060 162 A2
0142516)	MAZDA FZ   HONDA DW-1
HYUNDAI: 040000C90SG	KIA / HYUNDAI SP-IV/ SPH-IV
MERCEDES BENZ: 236.12	ZF: Lifeguard Fluid 6 (S671
MERCEDES BENZ: 236.14	090 255)
MERCEDES BENZ: 236.41	ZF: Lifeguard Fluid 8
Mitsubishi: SP-IV & ATF J-2	
JWS: 3324	

### APPLICATIONS

ATF S 41 is a synthetic automatic transmission oil, which has been especially developed for automatic gear boxes requiring low viscosity ATF. ATF S 41 ensures easy shifting under all operating temperatures, without unnecessary friction. Because of the low pour point and the high VI, ATF S 41 can be applied in a wide temperature range. Because of the excellent oxidation and thermal stability, ATF S 41 keeps its unique properties, so it easily meets the prescribed drain intervals. Mainly intended for the 6 or 8 speed automatic transmissions from ZF or other manufacturers, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid like Mercedes-Benz, Hyundai, Toyota. This transmission oil is very universal in use.

### AVAILABLE SIZE



### CHARACTERISTICS/SPECS

### UNIT

### AVERAGE VALUE

Density at 15 °C	kg/l	0.845
Viscosity 40 °C	mm <sup>2</sup> /s	31.00
Viscosity 100 °C	mm <sup>2</sup> /s	6.20
Viscosity Index		153.00
Brookfield Viscosity at -40 °C	mgKOH/g	9500.00
Color		Amber