
Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version number 1

Revision: 12.02.2015



Printing date 12.02.2015

Version number 1

Revision: 12.02.2015

| Trade name: 5W40 | PRO-TEC ULTRA | |
|---------------------------------------|---|----------------------------|
| | | (Contd. of page 1) |
| Hazard pictogram | ams | |
| GHS07 | | |
| Signal word Water | arning | |
| Hazard statem | | |
| H319 Causes s | serious eye irritation. | |
| | to aquatic life with long lasting effects. | |
| Precautionary st | | |
| P101 | If medical advice is needed, have product container | r or label at hand. |
| P102 | Keep out of reach of children. | |
| P280 | Wear protective gloves / eye protection. | |
| P273 | Avoid release to the environment. | |
| P264 | Wash thoroughly after handling. | |
| P305+P351+P3 | 338 IF IN EYES: Rinse cautiously with water for several lenses, if present and easy to do. Continue rinsing | al minutes. Remove contact |
| P337+P313 | If eye irritation persists: Get medical advice/attention | |
| P501 | Dispose of contents /container in accordance with I international regulations. | |
| 2.3 Other haza | | |
| Results of PBT | and vPvB assessment | |
| PBT: Not applie | cable. | |
| | | |

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients - 3.2

Mixtures

| Dangerous components: | | LEO 4000/ |
|--|---|----------------------|
| CAS: 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic | <mark>50-100%</mark> |
| EINECS: 265-157-1 | 🚸 Asp. Tox. 1, H304 | |
| Reg.nr.: 01-2119484627-25 | | 0 |
| CAS: 68037-01-4 | 1-decene, homopolymer, hydrogenated | 2.5-10% |
| NLP: 500-183-1 | 🚸 Asp. Tox. 1, H304 | 1 |
| Reg.nr.: 01-2119486452-34 | | |
| CAS: 64742-65-0 | Distillates (petroleum), solvent-dewaxed heavy paraffinic | 2.5-10% |
| EINECS: 265-169-7 | 🚸 Asp. Tox. 1, H304 | 1 |
| Reg.nr.: 01-2119471299-27 | | |
| CAS: 93819-94-4 | zin c bi s [O - (6 - m e t hyl he p tyl)] bi s [O - (s e c - b ut yl)] | 1-2.5% |
| EINECS: 298-577-9 | bis(dithiophosphate) | |
| Reg.nr.: 01-2119543726-33 | Xi R38-41; N R51/53 | |
| | Eye Dam. 1, H318; Aquatic Chronic 2, H411; | 1 |
| | 🚸 Skin Irrit. 2, H315 | 7 |
| CAS: 121158-58-5 | Dodecylphenol, mixed isomers (branched) | 0.1-1.0% |
| EC number: 310-154-3 | 🗙 Xn R62; 🗙 Xi R36/38; 🔥 R50/53 | |
| Reg.nr.: 01-2119513207-49 | | 1 |
| | Repr. 2, H361; Aquatic Acute 1, H400; Aquatic | 4 |
| | Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | |
| Additional information: For the second second | he wording of the listed risk phrases refer to section 16. | |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version number 1

Revision: 12.02.2015

(Contd. of page 2)

Trade name: 5W40 PRO-TEC ULTRA

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed If

swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, dry chemical, or foam. Water can be used to cool and protect exposed material.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Formation
- of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- Protective equipment:
 - Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Remove from the water surface (e.g. skim or suck off).
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Avoid the formation of oil haze.
- · Information about fire and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities ·

Storage:

• Requirements to be met by storerooms and receptacles: Store only in the original receptacle. • Information about storage in one common storage facility: Not required.

- Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version number 1

Revision: 12.02.2015

(Contd. of page 3)

Trade name: 5W40 PRO-TEC ULTRA

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.
- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work. ·
- Respiratory protection: Not required.
- Protection of hands:



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves · Material of gloves Nitrile rubber, NBR PVC gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling ·

Body protection: Protective work clothing

| SECTION 9: Physical and chem | ical properties |
|--|---|
| 9.1 Information on basic physical General Information Appearance: | and chemical properties . |
| Form: | Liquid |
| Colour: | Brown |
| · Odour: | Characteristic |
| Change in condition | |
| Boiling point/Boiling range: | Undetermined. |
| Flash point: | > 110 °C |
| Flammability (solid, gaseous): | Not applicable. |
| Self-igniting: | Product is not selfigniting. |
| Danger of explosion: | Product does not present an explosion hazard. |
| Explosion limits: | |
| Lower: | 0.6 Vol % |
| Upper: | 7.0 Vol % |

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version number 1

Revision: 12.02.2015

Trade name: 5W40 PRO-TEC ULTRA

| | | (Contd. of page 4) |
|---|--|--------------------|
| Density at 20 °C: | 0.856 g/cm ³ | |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol/wat | er): Not determined. | |
| Viscosity: | | |
| 40 °C | 88,4 mm²/s (ASTM D445) | |
| Solvent content: | | |
| Organic solvents: | 0.0 % | |
| 9.2 Other information | No further relevant information available. | |

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: To
- avoid thermal decomposition do not overheat.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available. · 12.3
- Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Remark:

This material is expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

- Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version number 1

Revision: 12.02.2015

(Contd. of page 5)

Trade name: 5W40 PRO-TEC ULTRA

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

| Void |
|-----------------|
| Void |
| |
| |
| Void |
| |
| Void |
| |
| No |
| Not applicable. |
| |
| Not applicable. |
| - |
| |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This information is based on our present knowledge. However, this shall not constitute a guarantee

for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
 H304 May be fatal if swallowed and

H304 May be fatal if swallowed and enters airways.

(Contd. on page 7)

4 0. 0. 7

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version number 1

Revision: 12.02.2015

Trade name: 5W40 PRO-TEC ULTRA

| | (Contd. of page 6) |
|--|--|
| H315 Causes skin irritation. | (|
| H318 Causes serious eye damage. | |
| H319 Causes serious eye irritation. | |
| H361 Suspected of damaging fertility or the unborn child.H400 Very toxic to aquatic life. | |
| H410 Very toxic to aquatic life with long lasting effects. | |
| H411 Toxic to aquatic life with long lasting effects. | |
| R36/38 Irritating to eyes and | an a |
| skin. R38 Irritating to skin. | |
| R41 Risk of serious damage to eyes. | |
| R50/53 Very toxic to aquatic organisms, may cause long-term adverse effect environment. | cts in the aquatic |
| R51/53 Toxic to aquatic organisms, may cause long -term adverse effects environment. | in the aquatic |
| R62 Possible risk of impaired fertility. | |
| Contact: Product safety department Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Repr. 2: Reproductive toxicity, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Sources 67/548/EEC 99/45/EEC EC/453-2010 | Agreement concerning the |