

**PREMIUM  
MOTOR OIL**  
**PASSENGER CARS & SUVs**



**QUALITY  
PERFORMANCE**

**MANUFACTURED IN BELGIUM**



**0W20 SX**  
**FULLY SYNTHETIC**

**PERFORMANCE LEVEL**

ACEA: A1/B1-10  
API: SN  
MB: 229.3/226.5  
VW: 502.00/505.00  
BMW: Longlife-01  
Renault: RN0700

**APPLICATIONS**

This product has been specifically developed to meet the challenging requirements for hybrid cars, where fuel economy and CO2 reduction is important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian (i.e. Honda, Toyota, Mitsubishi) passenger cars.

**AVAILABLE SIZE**



**CHARACTERISTICS/SPECS**

**UNIT**

**AVERAGE VALUE**

Density at 15 °C	kg/l	0.846
Viscosity 40 °C	mm <sup>2</sup> /s	46.70
Viscosity 100 °C	mm <sup>2</sup> /s	8.54
Viscosity Index		162.00
Flash Point COC	°C	230.00
Pour Point	°C	-48.00
Total Base Number	mgKOH/g	9.70
Sulphate Ash	%	1.22
Viscosity -35 °C	mPas	5320.00